

configuration

Overview

Textbox.io [editor](#) instances are configured through a configuration object, passed as a second argument when creating an editor via [replace](#), [replaceAll](#), [inline](#), or [inlineAll](#). Defining properties of a `configuration` object will override the configuration defaults supplied for any generated instances of [editor](#).

Configuration Object Properties

Note that all properties are optional. Defining a property overrides the editor default behavior.

autosubmit	Boolean	Specifies whether textboxio should handle form submission
basePath	String	Specifies the path to the textboxio resources folder
css	Object	Content CSS and styling application
codeview	Object	Code view feature
images	Object	Image handling & upload
links	Object	Content link validation
macros	Object	Built-in macro configuration
paste	Object	Content paste behavior
spelling	Object	Content spell checking service
ui	Object	Editor UI including toolbars, menus, etc.

Configuration Defaults

This following object will replicate the default configuration for all Textbox.io instances.

Implicit Configuration Defaults

```
var defaultConfig = {
  autosubmit: true,
  css : {
    stylesheets : [''],
    styles : [
      { rule: 'p',          text: 'block.p' },
      { rule: 'h1',        text: 'block.h1' },
      { rule: 'h2',        text: 'block.h2' },
      { rule: 'h3',        text: 'block.h3' },
      { rule: 'h4',        text: 'block.h4' },
      { rule: 'div',       text: 'block.div' },
      { rule: 'pre',       text: 'block.pre' }
    ]
  },
  codeview : {
    enabled: true,
    showButton: true
  },
  images : {
    allowLocal : true
  },
  languages : ['en', 'es', 'fr', 'de', 'pt', 'zh']
macros : {
  allowed : [ 'headings', 'lists', 'semantics', 'entities', 'hr', 'link' ]
}
  ui : {
    toolbar : {
      items : [ 'undo', 'insert', 'style', 'emphasis', 'align', 'listindent', 'format',
'tools' ]
    }
  }
};
```



Internationalization

Note that `text` properties are pre-configured with values like `block.p`. These string keys refer to the internationalized string label for that item. Using a pre-configured value means that the text value will be internationalized by `locale`.