

CSS

```
configuration
  css
```

The `configuration.css` property defines options related to editor rendering CSS and CSS classes/elements available in the styles menu.

Example Configuration

In this example, a simple `configuration` object is created that adds a rendering stylesheet to the editor, inline rendering CSS, and configures the styles available to apply.

```
var config = {
  css : {
    documentStyles : 'body { background: red; }',
    styles : [
      { rule : 'p' },
      { rule : 'h1.blue', text: 'Blue Heading 1' },
      { rule : '.green', text: 'Green Inline Style' }
    ],
    stylesheets : ['test.css'],
    showDocumentStyles : true
  }
};

var editor = textboxio.replace('#targetId', config);
```

Properties

Property	Type	Value
<code>documentStyles</code>	String	String of CSS for rendering editor content. Note This parameter is ignored when using inline editing (i.e. invoking the editor with <code>textboxio.inline()</code>)
<code>showDocumentStyles</code>	Boolean	Whether to show content style rules in the styles drop-down menu by default. Defaults to <code>false</code> . Full details on defining styles in content CSS is covered in the Using Your Own Document Styles article. Note <i>This parameter is ignored when using inline editing (i.e. invoking the editor with <code>textboxio.inline()</code>)</i> Note This API was introduced in Textbox.io release 2.4.1
<code>styles</code>	Array	An array of available styles definitions .
<code>stylesheets</code>	Array	An array of string paths to editor rendering stylesheets. <i>Note: this parameter is ignored when using inline editing (i.e. invoking the editor with <code>textboxio.inline()</code>)</i>