

# Basic ASP.NET Example Code

## ASPX Page

```
<%@ Page Language="C#" AutoEventWireup="true" CodeFile="BasicSample.aspx.cs" Inherits="basic_BasicSample"
ValidateRequest="false" %>
<%@ Register assembly="EditLiveJavaControl" namespace="EditLiveJavaControl" tagprefix="elj" %>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-
transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
  <title>Basic Example</title>
</head>
<body>
  <form id="form1" runat="server">
    <elj:EditLiveJava ID="EditLiveJava1" runat="server"
      DownloadDirectory="../../redistributables/editlivejava"
      ConfigurationFile="../../redistributables/editlivejava/sample_eljconfig.xml"
      Content="&lt;p&gt;Default editor content&lt;/p&gt;&lt;p&gt;More content&lt;/p&gt;"
    />
    <br />
    <asp:Button ID="Button1" runat="server" onclick="Button1_Click" Text="Button" />
    <br />
    <asp:TextBox ID="TextBox1" runat="server" Height="96px" TextMode="MultiLine" Width="252px" />
    <br />
  </form>
</body>
</html>
```

## C# Code-Behind

```
using System;
using System.Collections;
using System.Configuration;
using System.Data;
using System.Web;
using System.Web.Security;
using System.Web.UI;
using System.Web.UI.HtmlControls;
using System.Web.UI.WebControls;
using System.Web.UI.WebControls.WebParts;

public partial class basic_BasicSample : System.Web.UI.Page {
    protected void Button1_Click(object sender, EventArgs e) {
        TextBox1.Text = EditLiveJava1.Content;
    }
}
```